



FLEX-ANT

轻型的液体输送软管

- 食品级
- PVC管壁
- PVC加强筋、抗静电铜丝

介质



















构造:

软性PVC管壁、硬质PVC筋、镀铜钢丝

特性:

内壁光滑、透明管壁、达到EU标准食品级、柔软、抗静电铜丝

应用:

工业、农业或者供料系统中颗粒、粉尘的输送抽吸

温度范围:

0°C至+60°C

颜色:

透明, 白色筋

内径 毫米/mm	外径 毫米/mm	壁厚 毫米/mm	弯曲半径 毫米/mm	克重 千克/米 (kg/m)	负压 毫巴 (mbar)	正压 巴(bar)	物料号
30	36	3, 0	125	0, 411	0, 76	5, 0	5135030000
32	38	3, 0	130	0, 426	0, 76	5, 0	5135032000
35	42	3, 5	150	0, 492	0, 76	5, 0	5135035000
38	45	3, 5	160	0, 576	0, 76	5, 0	5135038000
40	47	3, 5	180	0,614	0, 76	5, 0	5135040000
45	53	4, 0	210	0, 733	0, 76	4, 0	5135045000
50	58	4, 0	230	0, 855	0, 76	4, 0	5135050000
55	63	4, 0	250	0, 963	0, 76	4, 0	5135055000
60	69	4, 5	270	1, 077	0, 76	4, 0	5135060000
63	72	4, 5	280	1, 176	0, 76	4, 0	5135063000
70	79	4, 5	300	1, 310	0, 76	3, 0	5135070000

VACUFLEX GmbH | Hessenring 8-12 64546 Mörfelden-Walldorf | Germany info@vacuflex.de | www.vacuflex.de

Alle technischen Daten, gemessen bei 23° C, dienen als allgemeine Orientierungswerte und unterliegen produktionsbedingten Toleranzen. Max. Betriebsdrücke gelten nur kurzzeitig. Technische Änderungen und Tel. +49 6105 9339 0 | Fax: +49 6105 9339 60 Farbabweichungen bleiben vorbehalten. Andere Ausführungen sind nach Vereinbarung lieferbar. Stand: 10/2025





内径 毫米/mm	外径 毫米/mm	壁厚 毫米/mm	弯曲半径 毫米/mm	克重 千克/米 (kg/m)	负压 毫巴 (mbar)	正压 巴(bar)	物料号
75	85	5, 0	340	1, 436	0, 76	3, 0	5135075000
80	90	5, 0	370	1, 617	0, 76	3, 0	5135080000
90	101	5, 5	405	1, 874	0, 76	2, 0	5135090000
100	112	6, 0	450	2, 279	0, 76	2, 0	5135100000
120	133	6, 5	550	2, 935	0, 70	2, 0	5135120000

依据要求可订制更多尺寸.

State: 18.10.2025